



FN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
COM	MO	TU	WE	TH	FR	SA	SU	FLTR	HOLD	1	2	3	4	5	6	7	8	9
CON	T1	P1	P2	P3	P4	1A	1B	1C	1D	1E	1F	1G	1H	1I	1J	1K	1L	1M

FN	19	20	21	22	23	24	25	26	27	28	29	30
COM	3	AM	FLTR	4	4	4	4	4	4	4	4	4
CON	3	AM	HOLD	5	4	4	4	4	4	4	4	4



- NOTES:
- VIEWING ANGLE: 6:00 O' CLOCK
  - DISPLAY MODE: POSITIVE/REFLECTIVE/TN TYPE
  - DRIVING VOLTAGE: 2.7V, DUTY:1/2, BIAS:1/2
  - OPERATING TEMP. : 0° C TO 50° C
  - STORAGE TEMP. : -10° C TO 60° C
  - CONNECTOR: PIN TYPE

6				<b>S-Tek Displays Cleveland, Ohio 44146</b>	
5				PART NO.	<b>GD-5360P</b>
4				TOLERANCES UNLESS OTHERWISE STATED	
3				.X ±0.20 ANGLES ±1°	
2	MODIFY LOGIC AND ICON	18/06-08	L. M. L.	DESIGN BY	Q B 26/05-08
1	MODIFY LOGIC	28/05-08	R. Y. Z.	CHECKED BY	
VER.	MODIFY CONTENTS	DATE	DESIGN	APP	BY
				COMPOSE TYPE:	
				<input type="checkbox"/> REV X-STEP:	# MM
				<input type="checkbox"/> LAB Y-STEP:	# MM
				APPLICATION:	
				<input type="checkbox"/> Instrument	<input type="checkbox"/> Audio Equipments
				<input type="checkbox"/> Telephone	<input type="checkbox"/> Automobile
				<input type="checkbox"/> Other Appliances	<input type="checkbox"/> Air-condition
				CUSTOMER: S-TEK	SAMPLE: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
				SHEET 1 OF 1	